

**APPLICATIONS** 

• Computer rooms

 Heating and air conditioning systems

 Building maintenance

Bakeries

 Humidistats calibration

# 597C1 Digital Humidity / Psychrometer

Small diameter tip (0.45 inches) for measuring dew point in air ducts and registers to prevent mold buildup.

Soft should strap carrying case.

39 inch cord to use and read in hard to reach spaces.



Œ

Comes hardwired with protoctive boot (A604)

**Turn over for** technical information and accessory part numbers.

#### **Features**

- Small diameter tip (0.45") for measuring dew point in air ducts and registers to prevent mold buildup
- Measure dewpoint, humidity, and wet bulb temperature to prevent mold buildup and condensation in HVAC systems.
- Relative humidity (RH) accuracy of +/-2% provides accurate reliable readings.
- Temperature -40° to 212°F (-40° to 100°C)

- Fast response time
- Data record function for maximum and minumum temperature or humodity reading
- Serial output through RS 232C
- 39" cable length, hard wired
- Data hold and Auto Power Off



#### TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

# Test Products International, Inc.

Headquarters: 9615 SW Allen Blvd. Beaverton, OR 97005 USA

503-502-9197 Fax: 503-520-1225 email:

info@tpi-thevalueleader.com

# **Test Products International, Ltd.**342 Bronte St. South

Unit 9 Milton, Ontario L9T 5B7 Canada

Fax: 905-693-0888 email:

905-693-8558

info@tpicanada.com

## Test Products International UK Ltd.

Longley House, East Park Crawley, West Sussex RH10 6AP England Tel: +44 (0)1293 561212 Fax: +44 (0)1293813465

contactus@tpieurope.com

### **595 Digital Humidity Thermometer**

### **SPECIFICATIONS**

Display	Dual digits LCD with function annunciation
Measurement	R/H(Relative Humidity) 0 ~ 100%
Temperature	-40°F ~ 212°F (-40°C ~ 100°C)
Measurement Range & Accuracy:	
Humidity	0% ~ 100% +/-(2% of reading +1% R/H) 0.1%RH
Temperature	$-40^{\circ}$ F ~ 212°F +/-(0.5% of reading +0.8°F + 3 digits)
	$-40^{\circ}$ C ~ $100^{\circ}$ C +/-(0.5% of reading +0.4°C + 3 digits)
Operating Temperature	32°F ~ 122°F (0°C ~50°C)
Operating Humidity	Less than 90% R/H
Powering	9V alkaline battery
Optional Accessories	A604 protective boot
	A901 soft shoulder strap carrying case

**Distributed By:** Accutherm International 18 Pickering Road Mulgrave 3170 Phone: +61 3 9763 6335

Email: sales@accutherm.com.au



To learn about the entire line of TPI products visit:

www.tpi-thevalueleader.com

P 597C1 0907 Copyright © 2004 Test Products International, Inc.