



# 725 Pocket Combustible Gas Detector

## APPLICATIONS

- Trace natural gas lines and fittings for leaks.
- Check gas applications for leaks.
- Check propane tanks, fitting lines, and heaters for leaks.
- Check gas generators for fuel leaks.
- Test confined spaces for gas build-up.



Actual size

## 725 Features

- Detects Combustible Gases Including: Natural Gas, Methane, Butane, Propane(LPG), Gasoline, Diesel, and Kerosene
- Fits in shirt pocket
- Auto zeros
- Visual and audible alarm
- Responds instantly

## LEAK LEVELS



Level 4: > 5,000ppm Methane

Level 3: > 4,000ppm Methane

Level 2: > 2,000ppm Methane

Level 1: > 1,000ppm Methane

Power: Green = Ready

Red = Replace Batteries

Turn over for technical information and accessory part numbers.

**The Value Leader™**

## OPERATING INSTRUCTIONS

- Remove sensor cap
- Press ON/OFF button
- LEDs will flash as the unit initializes; when the green LED above the ON/OFF button is lit, the unit is ready
- Upon detection an alarm will sound & the red LED will indicate the severity of the leak



visit us at [www.tpi-thevalueleader.com](http://www.tpi-thevalueleader.com)



**TECHNICAL  
SPECIFICATIONS  
AND  
ACCESSORIES**

Digital  
Multimeters •  
Clamp Meters •  
Hand-held  
Oscilloscopes •  
Refrigerant &  
Combustible Gas  
Leak Detectors •  
Temperature  
Testers • BNC  
Coax Cable •  
Connectors •  
Test Leads •  
Accessories

**Test Products  
International, Inc.**  
Headquarters:  
9615 SW Allen Blvd.  
Beaverton, OR 97005  
USA  
503-520-9197  
Fax: 503-520-1225  
email:  
info@tpi-the value leader.com

**Test Products  
International, Ltd.**  
342 Bronte St. South  
Unit 9  
Milton, Ontario L9T  
5B7  
Canada  
905-693-8558  
Fax: 905-693-0888  
email:  
info@tpicanada.com

**Test Products  
International UK Ltd.**  
Longley House, East Park  
Crawley, West Sussex  
RH10 6AP England  
Tel: +44 (0)1293 561212  
Fax: +44 (0)1293813465  
contact us@tpieurope.com

## 725 Pocket Combustible Gas Detector

### Instrument Specifications

Sensitivity:	> 1,000ppm combustible gas (Methane)
Operating Temp:	32° to 104°F (0° to 40° C)
Warm-up:	7-10 seconds
Response Time:	Instantaneous
Battery:	Two AAA
Power Consumption:	DC 20mA
Battery Life:	3 continuous hours
Overall Dimensions:	1.38" 5.0" x 0.75" (34.9 x 127 x 19.1)
Weight:	0.30 lb. (0.14 kg.)

***Distributed By: Accutherm International  
18 Pickering Road Mulgrave 3170***

***Phone: +61 3 9763 6335***

***Email: sales@accutherm.com.au***



To learn about the entire  
line of TPI products visit:

**www.tpi-thevalueleader.com**

L 725-1104

Copyright © 2004 Test Products International, Inc.