

# **775** Combination Carbon Monoxide & Combustion Gas Leak Detector

### New! Two Tools in One!

The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held affordable instrument.



The TPI 775 is a state-of-the-art Carbon Monoxide and Combustible Gas Leak Detector. It is the first of its kind to combine both detection technologies into one easy to use hand-held and affordable instrument.

- Easy to use
- One hand operation
- Auto zero
- Back light
- Visible and audible alarm

Turn over for technical information and accessory part numbers.

The Value Leader™

# **Sensor Specifications**

TypeResolutionRangeAccuracyLeak<50ppm</td>0-50,000ppm±10%CO1ppm0-2,000ppm±5ppm or 5%;<br/>whichever is greater



# **SPECIFICATION ACCESSORIES**

- Digital Multimeters
- · Clamp Meters
- · Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

#### **Test Products** International, Inc.

Headquarters: 9615 SW Allen Blvd. Beaverton, OR 97005 USA

503-520-9197 Fax: 503-520-1225 email:

info@tpi-thevalueleader.com

#### **Test Products** International, Ltd.

342 Bronte St. South Unit 9 Milton, Ontario L9T 5B7

Canada 905-693-8558 Fax: 905-693-0888 email:

info@tpicanada.com

#### Test Products **International UK Ltd.**

Longley House, East Park Crawley, West Sussex RH10 6AP England Tel: +44 (0)1293 561212 Fax: +44 (0)1293813465

contactus@tpieurope.com

775 Combustion Carbon Monoxide & **Combustion Gas Leak Detector** 

## **SPECIFICATIONS**

Alarms	Visual and Audible	
Response Time:		
CO	90% in 30 seconds	
Leak	Instantaneous	
Goose Neck Length	16" (406mm)	
Dimensions	9.5" x 2.9" x 2.2"	
	(240mm x 74mm x 55mm)	
Power	2 'C' Alkaline Batteries	
Power Consumption	About 400mW in typical use	
Operating and	32° to 120°F (0° to 50°C)	
Storage Temperature	,	
Warranty	3 years	
Standard Accessories	Soft Carrying Case	
	Manual	
	2 'C' Alkaline Batteries	
Optional Accessories	Earphones	

#### SENSOR SPECIFICATIONS

Type	Resolution	Range	Accuracy
Leak	<50ppm	0-50,000ppm	±10%
CO	1ppm	0-2,000ppm	±5ppm or 5%;
			whichever is greater

Distributed By: Accutherm International 18 Pickering Road Mulgrave 3170

Phone: +61 3 9763 6335

Email: sales@accutherm.com.au



To learn about the entire line of TPI products visit:

www.tpi-thevalueleader.com Copyright © 2004 Test Products International, Inc.